

Gatesplus

1300 121 666

www.gatesplus.com.au



Clamp fittings

Barrier Panels

Posts, end terminations, toe plates

Fasteners, tools & accessories

1300 121 666

www.gatesplus.com.au



SAFETY BARRIER SYSTEMS

Complete range of clamps, barrier panels, posts, rails, toe plates, fasteners and accessories for all sorts of safety barrier applications

The Kwikclamp [®] range of modular fittings, posts, rails, end terminations, barrier panels and accessories all comply with the design requirements of AS1657 and AS1428, the Australian Standards for safety barriers in a multitude of applications. All products are hot dip galvanised to comply with AS4680 and have a minimum of 500gsm zinc coating.


Clamp products are made from recycled steel resulting in a "green" steel product. Available in C42 and D48 sizes (other sizes supplied on special order – B34 and E60), Kwikclamp's fittings are made from malleable or ductile iron with case hardened 12mm long 304 grade stainless steel screws for extra durability, vibration and corrosion resistance in the toughest conditions.


Tube Size Guide

Size Reference	Tube OD (mm)	Nominal Size (mm)
B-34	33.7	25NB
C-42	42.4	32NB
D-48	48.3	40NB
E-60	60.3	50NB


Construction Guide


The following illustrations are a guide for installing different types of handrail systems.





Check with your designer or specifier before using these possible configurations for any given application.







SAFETY BARRIER SYSTEMS

All Kwikclamp barrier panel products are hot dip galvanised for longer life, not all items and sizes are held in stock

Kwikclamp products are used in a multitude of applications, initially designed for the safety barrier and hand rail markets; the modular nature of the clamps has given rise to very creative and highly functional applications that include ...

- Bikeway and pedestrian safety barrier systems
- Disability hand rails
- Trolley parking bays
- Playground equipment
- Road signs
- Retail displays & racking

- Exhibition stands & displays
- General signage
- Temporary shelters and buildings
- Fall prevention systems, commercial, industrial & factory safety barriers
- Machinery enclosures & guards
- Roof and walkway guard rails

There an almost infinite number of ways of using the Kwikclamp fittings, barrier panels and accessories to quickly and easily create rigid structures with minimal need for tools and labour. The simple, modular nature of Kwikclamp products makes for less expensive erection of barriers compared to traditional welded or ball type designs.

All Kwikclamp fittings, posts, rails and barrier panels have been independently tested to comply with AS1657 for 2.4m post spacing – the Australian Standard for fixed platforms walkways and stairways as well as complying with AS4680 – galvanising.



- Cost effective
- Fast to erect
- Best value modular system available certified to 2.4m widths
- TUV certified clamp fittings
- Panels and rails comply with AS1657 specifications





Some images in this brochure are used for illustration purposes only and may not be actual Kwikclamp products, any such images are used solely to illustrate generic industry product types and/or applications.



CLAMP FITTINGS

All clamp fittings are hot dip galvanised plus an extra protective top coating for longer life, not all items and sizes are held in stock

The Kwikclamp Clamp Range



- Not all clamps are available in all sizes check online or call 1300 121 666 for availability
- All specifications, designs and dimensions are subject to change without notice
- All Kwikclamp fittings use 12mm long 304 grade stainless screws for superior corrosion & vibration resistance



CLAMP FITTINGS

All clamp fittings are hot dip galvanised plus an extra protective top coating for longer life, not all items and sizes are held in stock



KWIKCLAMP DDA ASSIST CLAMP RANGE

Smooth inline handrail clamps designed to comply with AS1428 – disability access design guide.



Notes:-

- Not all clamps are available in all sizes check online or call 1300 121 666 for availability
- Powder coated finishes are available on special request (minimum order quantities and charges apply)
- Clamps must not be welded or cut
- All specifications, designs, dimensions and carton qtys are subject to change without notice
- Some product images are for illustration purposes only
- All Kwikclamp fittings use 12mm long 304 grade stainless steel screws for superior corrosion and vibration resistance



RAILS, POSTS, END TERMINATIONS

All pipe & plate products are hot dip galvanised for longer life, not all items and sizes are held in stock

Kwikclamp supplies a range of posts, rails, end terminations and toe plates in various lengths and configurations. The vast majority of safety handrails are 40NB medium pipe (48.3 OD x 3.2mm) with cranked post tops suited to AS1428 and Cycle Australia design guidelines. We can also have custom designs made for large scale projects where we are indeed very experienced in delivering top quality product at excellent value.

End terminations – panel type, "D" and "J" designs





Toe plates



100mm wide x 5mm, heavy galv, pre-drilled toe plates





Straight and cranked top posts – D48, matching rails in C42 and D48 sizes available

FASTENERS, TOOLS, ACCESSORIES

All the additional items needed to erect and complete a safety barrier and hand rail system.

Fasteners





Tools – all CR-V top quality



Reflective & Line Marking tape



- M12 x 100 heavy galv concrete anchor bolts
- Self-drilling hex head TEK screws 5g x 32mm, heavy galv
- M12 x 40m cuphead bolt, washer & nut
- All heavy hot dip galvanised
- Heavy duty 12mm socket handle
- Hex key 12mm socket
- Ultra-tough Allen keys 5/16" for C42 and D48 fittings

Single & double colour reflective tapes for applying to posts and rails for added visibility - *various colours & widths*

Single & double colours and luminescent line marking tapes

Some images in this brochure are used for illustration purposes only and may not be actual Kwikclamp products, any such images are used solely to illustrate generic industry product types and/or applications.



BARRIER PANELS

All barrier panel products are hot dip galvanised for longer life, not all items and sizes are held in stock

Barrier panels – all 1000mm high



Bikeway panels – same length top & bottom rails

- Designed for use with extend posts and 119 CROSS fittings
- End termination sections also available

Pedestrian panels – bottom rail is 50mm shorter than top rail

- Designed for use with 104 TEE joiner and 119 CROSS fittings
- 2400 and 1800mm width panels
- 40NB medium (3.2mm) top & bottom rails
- 12mm solid rod pickets, continuous weld of rod to rail
- Hot dip galv to exceed AS4680 after welding
- 36⁰ inclined versions available
- 2.4m wide panels are certified for AS1657 compliance

Kwikclamp barrier panels have been independently tested to comply with AS1657 and also comply with Cycling Australia design guidelines. Typical hot dip galv coating is around 90-120 microns – far in excess of the Australian Standard requirement of 70 microns (500gsm).

We can have any design, incline angle panel made to order, call us to enable us to help you get what you need for your projects.

1300 121 666



Lots of bikeway and pedestrian barrier applications – all sorts of designs are possible.



SAFETY BARRIER SYSTEMS

All Kwikclamp barrier products are hot dip galvanised for longer life, not all items and sizes are held in stock

AS1657 Compliance Certified, TUV Certified – quality you can rely on!

Kwikclamp barrier systems have been independently tested and certified by LMATS, a NATA registered testing authority, for compliance with AS1657 – the Australian Standard for the design, construction and installation of walkway and stairway barriers. Certification for panels and handrails at 2.4m post spacing for D48 (40NB) size rails, posts and fittings means that pedestrian and bikeway barriers and safety handrails can be erected at 2.4m post spacing:—

- Fewer posts, fasteners and fittings
- Less labour and faster installation times
- Far lower total cost than other modular barrier systems that can only be used in 1800 and 2000mm wide post spacing to comply with AS1657

A copy of the LMATS test report and AS1657 certification can be downloaded from the Kwikclamp website (www.kwikclamp.com.au). Check the website for other certifications that will become available from time to time.





Kwikclamp's supplier of our fittings has their fittings regularly tested and certified by TUV Rheinland as complying with applicable European standards – further evidence of the quality of the Kwikclamp range of modular barrier systems products.

So when you need a very competitive and complete system of superior clamps, barrier panels, posts, rails and fasteners, Kwikclamp has what you need backed with responsive, reliable service and distributors Australia wide. Find your nearest supplier online to or call us for assistance.





Proudly distributed by:

GatesPlus 1300 121 666